

**SILVERTHIN JSB055CP0****5.5 in Sealed Type C Thin Section Bearing****Specifications**

Bore (B)	5.500 in
Outside Diameter (D)	6.125 in
Width	5/16"
Land Diameter (L <sub>1</sub> )	5.731 in
Land Diameter (L <sub>2</sub> )	5.893 in
Approximate Weight	0.41 lbs
Separator	Brass; snapover separator
Precision Class	ABEC Class 1
Bearing Type	Radial Contact (Type C)
Seals, Shields	Buna N Rubber Seal
Unit System	Inch

**Load Capacities**


Static Radial Load	2,360 lbf
Dynamic Radial Load	985 lbf
Torque Max No Load	44 in-lbs

**Interchange**

Silverthin	<a href="#">JSB055CP0</a>	Kaydon	<a href="#">JB055CP0</a>	Kaydon	<a href="#">JB055CP0</a>	INA	<a href="#">CSCB0552RS</a>
SKF	<a href="#">FPCB5082RS1</a>	FAG	<a href="#">L10RA5082RSD</a>	NSK	<a href="#">NBC13907DD</a>	NTN	<a href="#">KRB139LL</a>
SSB	<a href="#">RJB055CP0</a>						

**Brass; snapover separator**

5/32" balls



1. Load capacities are not additive
2. The maximum shaft or housing fillet radius that the bearing corners will clear for this series is 0.040"
3. Race Width Tolerance: +0.000 -0.005"

**Also Available**

Open Angular Contact	<a href="#">SB055AR0</a>
Open Radial Contact	<a href="#">SB055CP0</a>
Open 4-Point Contact	<a href="#">SB055XP0</a>
Sealed 4-Point Contact	<a href="#">JSB055XP0</a>
Open Duplexed (Back-to-Back)	<a href="#">SB055BR0</a>
Open Duplexed (Face-to-Face)	<a href="#">SB055FR0</a>