

SILVERTHIN JSU040CP0**4 in Sealed Type C Thin Section Bearing****Specifications**

Bore (B)	4.000 in
Outside Diameter (D)	4.750 in
Width	1/2"
Land Diameter (L ₁)	4.277 in
Land Diameter (L ₂)	4.473 in
Approximate Weight	0.55 lbs
Separator	Brass; snapover separator
Precision Class	ABEC Class 1
Bearing Type	Radial Contact (Type C)
Seals, Shields	Buna N Rubber Seal
Unit System	Inch

Load Capacities


Static Radial Load	2,100 lbf
Dynamic Radial Load	1,075 lbf
Torque Max No Load	3 in-lbs

Interchange

Silverthin	JSU040CP0	Kaydon	JU040CP0	Kaydon	JU040CP0	INA	CSCU0402RS
SKF	FPCU4002RS1	FAG	L10SG4002RSD	NSK	NBC10112DD	NTN	KRJ040LL
SSB	RJU040CP0	RBC	JU040CP0*RBC				

Brass; snapover separator

3/16" balls



1. Load capacities are not additive
2. The maximum shaft or housing fillet radius that the bearing corners will clear for this series is 0.040"
3. Race Width Tolerance: +0.000 -0.005"

Also Available

Open Angular Contact	SC040AR0
Open Radial Contact	SC040CP0
Open 4-Point Contact	SC040XP0
Sealed 4-Point Contact	JSU040XP0
Open Duplexed (Back-to-Back)	SC040BR0
Open Duplexed (Face-to-Face)	SC040FR0