

SILVERTHIN JSU055CP0**5.5 in Sealed Type C Thin Section Bearing****Specifications**

Bore (B)	5.500 in
Outside Diameter (D)	6.250 in
Width	1/2"
Land Diameter (L ₁)	5.777 in
Land Diameter (L ₂)	5.973 in
Approximate Weight	0.74 lbs
Separator	Brass; snapover separator
Precision Class	ABEC Class 1
Bearing Type	Radial Contact (Type C)
Seals, Shields	Buna N Rubber Seal
Unit System	Inch

Load Capacities


Static Radial Load	2,831 lbf
Dynamic Radial Load	1,275 lbf
Torque Max No Load	5 in-lbs

Interchange

Silverthin	JSU055CP0	Kaydon	JU055CP0	Kaydon	JU055CP0	INA	CSCU0552RS
SKF	FPCU5082RS1	FAG	L10SG5082RSD	NSK	NBC13912DD	NTN	KRJ055LL
SSB	RJU055CP0	RBC	JU055CP0*RBC				

Brass; snapover separator

3/16" balls



1. Load capacities are not additive
2. The maximum shaft or housing fillet radius that the bearing corners will clear for this series is 0.040"
3. Race Width Tolerance: +0.000 -0.005"

Also Available

Open Angular Contact	SC055AR0
Open Radial Contact	SC055CP0
Open 4-Point Contact	SC055XP0
Sealed 4-Point Contact	JSU055XP0
Open Duplexed (Back-to-Back)	SC055BR0
Open Duplexed (Face-to-Face)	SC055FR0