

SILVERTHIN JSU060CP0**6 in Sealed Type C Thin Section Bearing****Specifications**

Bore (B)	6.000 in
Outside Diameter (D)	6.750 in
Width	1/2"
Land Diameter (L ₁)	6.277 in
Land Diameter (L ₂)	6.473 in
Approximate Weight	0.81 lbs
Separator	Brass; snapover separator
Precision Class	ABEC Class 1
Bearing Type	Radial Contact (Type C)
Seals, Shields	Buna N Rubber Seal
Unit System	Inch

Load Capacities


Static Radial Load	3,071 lbf
Dynamic Radial Load	1,335 lbf
Torque Max No Load	6 in-lbs

Interchange

Silverthin	JSU060CP0	Kaydon	JU060CP0	Kaydon	JU060CP0	INA	CSCU0602RS
SKF	FPCU6002RS1	FAG	L10SG6002RSD	NSK	NBC15212DD	NTN	KRJ060LL
SSB	RJU060CP0	RBC	JU060CP0*RBC				

Brass; snapover separator

3/16" balls



1. Load capacities are not additive
2. The maximum shaft or housing fillet radius that the bearing corners will clear for this series is 0.040"
3. Race Width Tolerance: +0.000 -0.005"

Also Available

Open Angular Contact	SC060AR0
Open Radial Contact	SC060CP0
Open 4-Point Contact	SC060XP0
Sealed 4-Point Contact	JSU060XP0
Open Duplexed (Back-to-Back)	SC060BR0
Open Duplexed (Face-to-Face)	SC060FR0