

SILVERTHIN JSU070CP0**7 in Sealed Type C Thin Section Bearing****Specifications**

Bore (B)	7.000 in
Outside Diameter (D)	7.750 in
Width	1/2"
Land Diameter (L ₁)	7.277 in
Land Diameter (L ₂)	7.473 in
Approximate Weight	0.93 lbs
Separator	Brass; snapover separator
Precision Class	ABEC Class 1
Bearing Type	Radial Contact (Type C)
Seals, Shields	Buna N Rubber Seal
Unit System	Inch

Load Capacities


Static Radial Load	3,551 lbf
Dynamic Radial Load	1,455 lbf
Torque Max No Load	8 in-lbs

Interchange

Silverthin	JSU070CP0	Kaydon	JU070CP0	Kaydon	JU070CP0	INA	CSCU0702RS
SKF	FPCU7002RS1	FAG	L10SG7002RSD	NSK	NBC17712DD	NTN	KRJ070LL
SSB	RJU070CP0	RBC	JU070CP0*RBC				

Brass; snapover separator

3/16" balls



1. Load capacities are not additive
2. The maximum shaft or housing fillet radius that the bearing corners will clear for this series is 0.040"
3. Race Width Tolerance: +0.000 -0.005"

Also Available

Open Angular Contact	SC070AR0
Open Radial Contact	SC070CP0
Open 4-Point Contact	SC070XP0
Sealed 4-Point Contact	JSU070XP0
Open Duplexed (Back-to-Back)	SC070BR0
Open Duplexed (Face-to-Face)	SC070FR0