

SILVERTHIN JSU080CP0**8 in Sealed Type C Thin Section Bearing****Specifications**

Bore (B)	8.000 in
Outside Diameter (D)	8.750 in
Width	1/2"
Land Diameter (L ₁)	8.277 in
Land Diameter (L ₂)	8.473 in
Approximate Weight	1.06 lbs
Separator	Brass; snapover separator
Precision Class	ABEC Class 1
Bearing Type	Radial Contact (Type C)
Seals, Shields	Buna N Rubber Seal
Unit System	Inch

Load Capacities


Static Radial Load	4,031 lbf
Dynamic Radial Load	1,570 lbf
Torque Max No Load	10 in-lbs

Interchange

Silverthin	JSU080CP0	Kaydon	JU080CP0	Kaydon	JU080CP0	INA	CSCU0802RS
SKF	FPCU8002RS1	FAG	L10SG8002RSD	NSK	NBC20312DD	NTN	KRJ080LL
SSB	RJU080CP0	RBC	JU080CP0*RBC				

Brass; snapover separator

3/16" balls



1. Load capacities are not additive
2. The maximum shaft or housing fillet radius that the bearing corners will clear for this series is 0.040"
3. Race Width Tolerance: +0.000 -0.005"

Also Available

Open Angular Contact	SC080AR0
Open Radial Contact	SC080CP0
Open 4-Point Contact	SC080XP0
Sealed 4-Point Contact	JSU080XP0
Open Duplexed (Back-to-Back)	SC080BR0
Open Duplexed (Face-to-Face)	SC080FR0