

SILVERTHIN JSU090CP0**9 in Sealed Type C Thin Section Bearing****Specifications**

Bore (B)	9.000 in
Outside Diameter (D)	9.750 in
Width	1/2"
Land Diameter (L ₁)	9.277 in
Land Diameter (L ₂)	9.473 in
Approximate Weight	1.18 lbs
Separator	Brass; snapover separator
Precision Class	ABEC Class 1
Bearing Type	Radial Contact (Type C)
Seals, Shields	Buna N Rubber Seal
Unit System	Inch

Load Capacities


Static Radial Load	4,511 lbf
Dynamic Radial Load	1,680 lbf
Torque Max No Load	13 in-lbs

Interchange

Silverthin	JSU090CP0	Kaydon	JU090CP0	Kaydon	JU090CP0	INA	CSCU0902RS
SKF	FPCU9002RS1	FAG	L10SG9002RSD	NSK	NBC22812DD	NTN	KRJ090LL
SSB	RJU090CP0	RBC	JU090CP0*RBC				

Brass; snapover separator

3/16" balls



1. Load capacities are not additive
2. The maximum shaft or housing fillet radius that the bearing corners will clear for this series is 0.040"
3. Race Width Tolerance: +0.000 -0.005"

Also Available

Open Angular Contact	SC090AR0
Open Radial Contact	SC090CP0
Open 4-Point Contact	SC090XP0
Sealed 4-Point Contact	JSU090XP0
Open Duplexed (Back-to-Back)	SC090BR0
Open Duplexed (Face-to-Face)	SC090FR0