

SILVERTHIN JSU120CP0**12 in Sealed Type C Thin Section Bearing****Specifications**

Bore (B)	12.000 in
Outside Diameter (D)	12.750 in
Width	1/2"
Land Diameter (L ₁)	12.277 in
Land Diameter (L ₂)	12.473 in
Approximate Weight	1.56 lbs
Separator	Brass; snapover separator
Precision Class	ABEC Class 1
Bearing Type	Radial Contact (Type C)
Seals, Shields	Buna N Rubber Seal
Unit System	Inch

Load Capacities


Static Radial Load	5,950 lbf
Dynamic Radial Load	1,975 lbf
Torque Max No Load	23 in-lbs

Interchange

Silverthin	JSU120CP0	Kaydon	JU120CP0	Kaydon	JU120CP0	INA	CSCU1202RS
SKF	FPCU12002RS1	FAG	L10SG12002RSD	NSK	NBC30412DD	NTN	KRJ120LL
SSB	RJU120CP0	RBC	JU120CP0*RBC				

Brass; snapover separator

3/16" balls



1. Load capacities are not additive
2. The maximum shaft or housing fillet radius that the bearing corners will clear for this series is 0.040"
3. Race Width Tolerance: +0.000 -0.005"

Also Available

Open Angular Contact	SC120AR0
Open Radial Contact	SC120CP0
Open 4-Point Contact	SC120XP0
Sealed 4-Point Contact	JSU120XP0
Open Duplexed (Back-to-Back)	SC120BR0
Open Duplexed (Face-to-Face)	SC120FR0