

SILVERTHIN SA045AR0**4.5 in Open Type A Thin Section Bearing****Specifications**

Bore (B)	4.500 in
Outside Diameter (D)	5.000 in
Width	1/4"
Land Diameter (L ₁)	4.686 in
Land Diameter (L ₂)	4.814 in
Land Diameter (L ₃)	4.865 in
Approximate Weight	0.22 lbs
Separator	Brass; one piece pocket separator
Precision Class	ABEC Class 1
Bearing Type	Angular Contact (Type A)
Seals, Shields	None (Open)
Unit System	Inch

Load Capacities


Static Radial Load	1,660 lbf
Dynamic Radial Load	635 lbf
Static Thrust Load	4,810 lbf
Dynamic Thrust Load	1,580 lbf

Interchange

Silverthin	SA045AR0	Kaydon	KA045AR0	Kaydon	KA045AR0	INA	CSEA045
SKF	FPAA408	FAG	L15QA408	NSK	NBA11406	NTN	KYA045
SSB	RA045AR0	RBC	KA045AR0*RBC				

Brass; one piece pocket separator

1/8" balls



1. Load capacities are not additive
2. The maximum shaft or housing fillet radius that the bearing corners will clear for this series is 0.025"
3. Race Width Tolerance: +0.000 -0.005"

Also Available

Open Radial Contact	SA045CP0
Open 4-Point Contact	SA045XP0
Sealed Radial Contact	JSA045CP0
Sealed 4-Point Contact	JSA045XP0
Open Duplexed (Back-to-Back)	SA045BR0
Open Duplexed (Face-to-Face)	SA045FR0