

SILVERTHIN SC045CP0**4.5 in Open Type C Thin Section Bearing****Specifications**

Bore (B)	4.500 in
Outside Diameter (D)	5.250 in
Width	3/8"
Land Diameter (L ₁)	4.777 in
Land Diameter (L ₂)	4.973 in
Approximate Weight	0.45 lbs
Separator	Brass; snapover separator
Precision Class	ABEC Class 1
Bearing Type	Radial Contact (Type C)
Seals, Shields	None (Open)
Unit System	Inch

Load Capacities


Static Radial Load	2,340 lbf
Dynamic Radial Load	1,145 lbf

Interchange

Silverthin	SC045CP0	Kaydon	KC045CP0	Kaydon	KC045CP0	INA	CSCC045
SKF	FPCC408	FAG	L10SA408	NSK	NBC11409	NTN	KRC045
SSB	RC045CP0	RBC	KC045CP0*RBC				

Brass; snapover separator

3/16" balls



1. Load capacities are not additive
2. The maximum shaft or housing fillet radius that the bearing corners will clear for this series is 0.040"
3. Race Width Tolerance: +0.000 -0.005"

Also Available

Open Angular Contact	SC045AR0
Open 4-Point Contact	SC045XP0
Sealed Radial Contact	JSU045CP0
Sealed 4-Point Contact	JSU045XP0
Open Duplexed (Back-to-Back)	SC045BR0
Open Duplexed (Face-to-Face)	SC045FR0