

SILVERTHIN SC047XP0**4.75 in Open Type X Thin Section Bearing****Specifications**

Bore (B)	4.750 in
Outside Diameter (D)	5.500 in
Width	3/8"
Land Diameter (L ₁)	5.027 in
Land Diameter (L ₂)	5.223 in
Approximate Weight	0.50 lbs
Separator	Brass; snapover separator
Precision Class	ABEC Class 1
Bearing Type	4-Point Contact (Type X)
Seals, Shields	None (Open)
Unit System	Inch

Load Capacities


Static Radial Load	2,460 lbf
Dynamic Radial Load	1,555 lbf
Static Thrust Load	6,160 lbf
Dynamic Thrust Load	2,460 lbf
Static Moment Load	6,320 in-lbs
Dynamic Moment Load	2,990 in-lbs

Interchange

Silverthin	SC047XP0	Kaydon	KC047XP0	Kaydon	KC047XP0	INA	CSXC047
SKF	FPXC412	FAG	L18SA412	NSK	NBX12009	NTN	KXC047
SSB	RC047XP0	RBC	KC047XP0*RBC				

Brass; snapover separator

3/16" balls



1. Load capacities are not additive
2. The maximum shaft or housing fillet radius that the bearing corners will clear for this series is 0.040"
3. Race Width Tolerance: +0.000 -0.005"

Also Available

Open Angular Contact	SC047AR0
Open Radial Contact	SC047CP0
Sealed Radial Contact	JSU047CP0
Sealed 4-Point Contact	JSU047XP0
Open Duplexed (Back-to-Back)	SC047BR0
Open Duplexed (Face-to-Face)	SC047FR0