

SILVERTHIN SC050CP0**5 in Open Type C Thin Section Bearing****Specifications**

Bore (B)	5.000 in
Outside Diameter (D)	5.750 in
Width	3/8"
Land Diameter (L ₁)	5.277 in
Land Diameter (L ₂)	5.473 in
Approximate Weight	0.48 lbs
Separator	Brass; snapover separator
Precision Class	ABEC Class 1
Bearing Type	Radial Contact (Type C)
Seals, Shields	None (Open)
Unit System	Inch

Load Capacities


Static Radial Load	2,591 lbf
Dynamic Radial Load	1,210 lbf

Interchange

Silverthin	SC050CP0	Kaydon	KC050CP0	Kaydon	KC050CP0	INA	CSCC050
SKF	FPCC500	FAG	L10SA500	NSK	NBC12709	NTN	KRC050
SSB	RC050CP0	RBC	KC050CP0*RBC				

Brass; snapover separator

3/16" balls



1. Load capacities are not additive
2. The maximum shaft or housing fillet radius that the bearing corners will clear for this series is 0.040"
3. Race Width Tolerance: +0.000 -0.005"

Also Available

Open Angular Contact	SC050AR0
Open 4-Point Contact	SC050XP0
Sealed Radial Contact	JSU050CP0
Sealed 4-Point Contact	JSU050XP0
Open Duplexed (Back-to-Back)	SC050BR0
Open Duplexed (Face-to-Face)	SC050FR0