

SILVERTHIN SC055CP0**5.5 in Open Type C Thin Section Bearing****Specifications**

Bore (B)	5.500 in
Outside Diameter (D)	6.250 in
Width	3/8"
Land Diameter (L ₁)	5.777 in
Land Diameter (L ₂)	5.973 in
Approximate Weight	0.50 lbs
Separator	Brass; snapover separator
Precision Class	ABEC Class 1
Bearing Type	Radial Contact (Type C)
Seals, Shields	None (Open)
Unit System	Inch

Load Capacities


Static Radial Load	2,831 lbf
Dynamic Radial Load	1,275 lbf

Interchange

Silverthin	SC055CP0	Kaydon	KC055CP0	Kaydon	KC055CP0	INA	CSCC055
SKF	FPCC508	FAG	L10SA508	NSK	NBC13909	NTN	KRC055
SSB	RC055CP0	RBC	KC055CP0*RBC				

Brass; snapover separator

3/16" balls



1. Load capacities are not additive
2. The maximum shaft or housing fillet radius that the bearing corners will clear for this series is 0.040"
3. Race Width Tolerance: +0.000 -0.005"

Also Available

Open Angular Contact	SC055AR0
Open 4-Point Contact	SC055XP0
Sealed Radial Contact	JSU055CP0
Sealed 4-Point Contact	JSU055XP0
Open Duplexed (Back-to-Back)	SC055BR0
Open Duplexed (Face-to-Face)	SC055FR0