

SILVERTHIN SC110XP0**11 in Open Type X Thin Section Bearing****Specifications**

Bore (B)	11.000 in
Outside Diameter (D)	11.750 in
Width	3/8"
Land Diameter (L ₁)	11.277 in
Land Diameter (L ₂)	11.473 in
Approximate Weight	1.16 lbs
Separator	Brass; snapover separator
Precision Class	ABEC Class 1
Bearing Type	4-Point Contact (Type X)
Seals, Shields	None (Open)
Unit System	Inch

Load Capacities


Static Radial Load	5,470 lbf
Dynamic Radial Load	2,495 lbf
Static Thrust Load	13,680 lbf
Dynamic Thrust Load	4,180 lbf
Static Moment Load	31,110 in-lbs
Dynamic Moment Load	10,650 in-lbs

Interchange

Silverthin	SC110XP0	Kaydon	KC110XP0	Kaydon	KC110XP0	INA	CSXC110
SKF	FPXC1100	FAG	L18SA1100	NSK	NBX27909	NTN	KXC110
SSB	RC110XP0	RBC	KC110XP0*RBC				

Brass; snapover separator

3/16" balls



1. Load capacities are not additive
2. The maximum shaft or housing fillet radius that the bearing corners will clear for this series is 0.040"
3. Race Width Tolerance: +0.000 -0.005"

Also Available

Open Angular Contact	SC110AR0
Open Radial Contact	SC110CP0
Sealed Radial Contact	JSU110CP0
Sealed 4-Point Contact	JSU110XP0
Open Duplexed (Back-to-Back)	SC110BR0
Open Duplexed (Face-to-Face)	SC110FR0