

SILVERTHIN SC200XP0**20 in Open Type X Thin Section Bearing****Specifications**

Bore (B)	20.000 in
Outside Diameter (D)	20.750 in
Width	3/8"
Land Diameter (L ₁)	20.277 in
Land Diameter (L ₂)	20.473 in
Approximate Weight	2.16 lbs
Separator	Brass; snapover separator
Precision Class	ABEC Class 1
Bearing Type	4-Point Contact (Type X)
Seals, Shields	None (Open)
Unit System	Inch

Load Capacities


Static Radial Load	9,800 lbf
Dynamic Radial Load	3,490 lbf
Static Thrust Load	24,500 lbf
Dynamic Thrust Load	6,170 lbf
Static Moment Load	99,830 in-lbs
Dynamic Moment Load	26,695 in-lbs

Interchange

Silverthin	SC200XP0	Kaydon	KC200XP0	Kaydon	KC200XP0	INA	CSXC200
SKF	FPXC2000	FAG	L18SA2000	NSK	NBX50809	NTN	KXC200
SSB	RC200XP0	RBC	KC200XP0*RBC				

Brass; snapover separator

3/16" balls



1. Load capacities are not additive
2. The maximum shaft or housing fillet radius that the bearing corners will clear for this series is 0.040"
3. Race Width Tolerance: +0.000 -0.005"

Also Available

Open Angular Contact	SC200ARO
Open Radial Contact	SC200CPO
Open Duplexed (Back-to-Back)	SC200BRO
Open Duplexed (Face-to-Face)	SC200FRO