

SILVERTHIN SF040AR0**4 in Open Type A Thin Section Bearing****Specifications**

Bore (B)	4.000 in
Outside Diameter (D)	5.500 in
Width	3/4"
Land Diameter (L ₁)	4.555 in
Land Diameter (L ₂)	4.945 in
Land Diameter (L ₃)	5.115 in
Approximate Weight	1.90 lbs
Separator	Brass; one piece pocket separator
Precision Class	ABEC Class 1
Bearing Type	Angular Contact (Type A)
Seals, Shields	None (Open)
Unit System	Inch

Load Capacities


Static Radial Load	6,350 lbf
Dynamic Radial Load	3,735 lbf
Static Thrust Load	18,340 lbf
Dynamic Thrust Load	8,420 lbf

Interchange

Silverthin	SF040AR0	Kaydon	KF040AR0
SKF	FPAF400	FAG	L15VA400
SSB	RF040AR0	RBC	KF040AR0*RBC

Brass; one piece pocket separator

3/8" balls



1. Load capacities are not additive
2. The maximum shaft or housing fillet radius that the bearing corners will clear for this series is 0.080"
3. Race Width Tolerance: +0.000 -0.005"

Also Available

Open Radial Contact	SF040CP0
Open 4-Point Contact	SF040XP0
Open Duplexed (Back-to-Back)	SF040BR0
Open Duplexed (Face-to-Face)	SF040FR0