

SILVERTHIN SF045XP0**4.5 in Open Type X Thin Section Bearing****Specifications**

Bore (B)	4.500 in
Outside Diameter (D)	6.000 in
Width	3/4"
Land Diameter (L ₁)	5.060 in
Land Diameter (L ₂)	5.445 in
Approximate Weight	2.10 lbs
Separator	Brass; snapover separator
Precision Class	ABEC Class 1
Bearing Type	4-Point Contact (Type X)
Seals, Shields	None (Open)
Unit System	Inch

Load Capacities


Static Radial Load	5,930 lbf
Dynamic Radial Load	4,925 lbf
Static Thrust Load	14,810 lbf
Dynamic Thrust Load	7,300 lbf
Static Moment Load	15,550 in-lbs
Dynamic Moment Load	9,695 in-lbs

Interchange

Silverthin	SF045XP0	Kaydon	KF045XP0	Kaydon	KF045XP0	INA	CSXF045
SKF	FPXF408	FAG	L18VA408	NSK	NBX11419	NTN	KXF045
SSB	RF045XP0	RBC	KF045XP0*RBC				

Brass; snapover separator

3/8" balls



1. Load capacities are not additive
2. The maximum shaft or housing fillet radius that the bearing corners will clear for this series is 0.080"
3. Race Width Tolerance: +0.000 -0.005"

Also Available

Open Angular Contact	SF045AR0
Open Radial Contact	SF045CP0
Open Duplexed (Back-to-Back)	SF045BR0
Open Duplexed (Face-to-Face)	SF045FR0