

SILVERTHIN SF055CP0**5.5 in Open Type C Thin Section Bearing****Specifications**

Bore (B)	5.500 in
Outside Diameter (D)	7.000 in
Width	3/4"
Land Diameter (L ₁)	6.055 in
Land Diameter (L ₂)	6.445 in
Approximate Weight	2.50 lbs
Separator	Brass; snapover separator
Precision Class	ABEC Class 1
Bearing Type	Radial Contact (Type C)
Seals, Shields	None (Open)
Unit System	Inch

Load Capacities


Static Radial Load	7,050 lbf
Dynamic Radial Load	4,115 lbf

Interchange

Silverthin	SF055CP0	Kaydon	KF055CP0	Kaydon	KF055CP0	INA	CSCF055
SKF	FPCF508	FAG	L10VA508	NSK	NBC13919	NTN	KRF055
SSB	RF055CP0	RBC	KF055CP0*RBC				

Brass; snapover separator

3/8" balls



1. Load capacities are not additive
2. The maximum shaft or housing fillet radius that the bearing corners will clear for this series is 0.080"
3. Race Width Tolerance: +0.000 -0.005"

Also Available

Open Angular Contact	SF055AR0
Open 4-Point Contact	SF055XP0
Open Duplexed (Back-to-Back)	SF055BR0
Open Duplexed (Face-to-Face)	SF055FR0