

SILVERTHIN SF060AR0**6 in Open Type A Thin Section Bearing****Specifications**

Bore (B)	6.000 in
Outside Diameter (D)	7.500 in
Width	3/4"
Land Diameter (L ₁)	6.555 in
Land Diameter (L ₂)	6.945 in
Land Diameter (L ₃)	7.113 in
Approximate Weight	2.70 lbs
Separator	Brass; one piece pocket separator
Precision Class	ABEC Class 1
Bearing Type	Angular Contact (Type A)
Seals, Shields	None (Open)
Unit System	Inch

Load Capacities


Static Radial Load	9,040 lbf
Dynamic Radial Load	4,530 lbf
Static Thrust Load	26,100 lbf
Dynamic Thrust Load	10,650 lbf

Interchange

Silverthin	SF060AR0	Kaydon	KF060AR0
SKF	FPAF600	FAG	L15VA600
SSB	RF060AR0	RBC	KF060AR0*RBC

Brass; one piece pocket separator

3/8" balls



1. Load capacities are not additive
2. The maximum shaft or housing fillet radius that the bearing corners will clear for this series is 0.080"
3. Race Width Tolerance: +0.000 -0.005"

Also Available

Open Radial Contact	SF060CP0
Open 4-Point Contact	SF060XP0
Open Duplexed (Back-to-Back)	SF060BR0
Open Duplexed (Face-to-Face)	SF060FR0