

SILVERTHIN SF100AR0**10 in Open Type A Thin Section Bearing****Specifications**

Bore (B)	10.000 in
Outside Diameter (D)	11.500 in
Width	3/4"
Land Diameter (L ₁)	10.555 in
Land Diameter (L ₂)	10.945 in
Land Diameter (L ₃)	11.106 in
Approximate Weight	4.30 lbs
Separator	Brass; one piece pocket separator
Precision Class	ABEC Class 1
Bearing Type	Angular Contact (Type A)
Seals, Shields	None (Open)
Unit System	Inch

Load Capacities


Static Radial Load	14,420 lbf
Dynamic Radial Load	5,890 lbf
Static Thrust Load	41,620 lbf
Dynamic Thrust Load	14,530 lbf

Interchange

Silverthin	SF100AR0	Kaydon	KF100AR0
SKF	FPAF1000	FAG	L15VA1000
SSB	RF100AR0	RBC	KF100AR0*RBC

Brass; one piece pocket separator

3/8" balls



1. Load capacities are not additive
2. The maximum shaft or housing fillet radius that the bearing corners will clear for this series is 0.080"
3. Race Width Tolerance: +0.000 -0.005"

Also Available

Open Radial Contact	SF100CP0
Open 4-Point Contact	SF100XP0
Open Duplexed (Back-to-Back)	SF100BR0
Open Duplexed (Face-to-Face)	SF100FR0