

**SILVERTHIN SF200AR0****20 in Open Type A Thin Section Bearing****Specifications**

Bore (B)	20.000 in
Outside Diameter (D)	21.500 in
Width	3/4"
Land Diameter (L <sub>1</sub> )	20.555 in
Land Diameter (L <sub>2</sub> )	20.945 in
Land Diameter (L <sub>3</sub> )	21.092 in
Approximate Weight	8.90 lbs
Separator	Brass; one piece pocket separator
Precision Class	ABEC Class 1
Bearing Type	Angular Contact (Type A)
Seals, Shields	None (Open)
Unit System	Inch

**Load Capacities**


Static Radial Load	28,100 lbf
Dynamic Radial Load	8,560 lbf
Static Thrust Load	81,120 lbf
Dynamic Thrust Load	22,680 lbf

**Interchange**

Silverthin	SF200AR0	Kaydon	KF200AR0
SKF	FPAF2000	FAG	L15VA2000
SSB	RF200AR0	RBC	KF200AR0*RBC

**Brass; one piece pocket separator**

3/8" balls



1. Load capacities are not additive
2. The maximum shaft or housing fillet radius that the bearing corners will clear for this series is 0.080"
3. Race Width Tolerance: +0.000 -0.005"

**Also Available**

Open Radial Contact	SF200CP0
Open 4-Point Contact	SF200XP0
Open Duplexed (Back-to-Back)	SF200BR0
Open Duplexed (Face-to-Face)	SF200FR0