

SILVERTHIN SG040CP0**4 in Open Type C Thin Section Bearing****Specifications**

Bore (B)	4.000 in
Outside Diameter (D)	6.000 in
Width	1"
Land Diameter (L ₁)	4.742 in
Land Diameter (L ₂)	5.258 in
Approximate Weight	3.60 lbs
Separator	Brass; snapover separator
Precision Class	ABEC Class 1
Bearing Type	Radial Contact (Type C)
Seals, Shields	None (Open)
Unit System	Inch

Load Capacities


Static Radial Load	8,210 lbf
Dynamic Radial Load	6,115 lbf

Interchange

Silverthin	SG040CP0	Kaydon	KG040CP0	Kaydon	KG040CP0	INA	CSCG040
SKF	FPCG400	FAG	L10WA300	NSK	NBC10125	NTN	KRG040
SSB	RG040CP0	RBC	KG040CP0*RBC				

Brass; snapover separator

1/2" balls



1. Load capacities are not additive
2. The maximum shaft or housing fillet radius that the bearing corners will clear for this series is 0.080"
3. Race Width Tolerance: +0.000 -0.005"

Also Available

Open Angular Contact	SG040AR0
Open 4-Point Contact	SG040XP0
Open Duplexed (Back-to-Back)	SG040BR0
Open Duplexed (Face-to-Face)	SG040FR0