
SILVERTHINSK6-22NZ

Overall Dimensions

Outside diameter of outer ring (D_o)	25.510 in
Internal diameter on outer ring (D _i)	21.340 in
External diameter on outer ring (D _r)	22.990 in
Inside diameter of inner ring (d _i)	17.600 in
External diameter on inner ring (d_o)	21.260 in
Approximate Weight	90.00 lbs

Internal Gear Slewing Ring Bearing



Gear Data ($\alpha = 20^{\circ}$)		Mounting Holes	
Pitch diameter of gear ([0 ₂) 18.000 ir	Inner Ring Bolt Circle (L _i)	19.630 in
Diametral pitch (P _d)	4	Inner Ring Hole Count	15
Max Gear Tooth Load (F	2) 6,530 lbs	outer Ring Bolt Circle (L _o)	24.380 in
Number of Teeth (Z_2)	72	2 Outer Ring Hole Count	10
Also Available		Load Capacities	
14 SD Tooth Mating Pinio	on SP1629-14	Moment Rating	33,630 ft-lbs
17 SD Tooth Mating Pinio	on SP1629-17	7	
Interchange			
Rotek L6-22NS	ZAvon 721 MB1Kay	rdon RK6-22N1Z	

866.294.5841 425.222.7535

35 sales@silverthin.com

8152 - 304th Ave. S.E. PO Box 5012 Preston, WA 98050-5012 USA

Copyright © 2024 All rights reserved by Silverthin