
SILVERTHINSK6-25NZ

Overall Dimensions

Outside diameter of outer ring (D_o)	29.450 in
Internal diameter on outer ring (D _i)	25.280 in
External diameter on outer ring (D _r)	26.930 in
Inside diameter of inner ring (d _i)	21.600 in
External diameter on inner ring (d _o)	25.200 in
Approximate Weight	106.00 lbs

Internal Gear Slewing Ring Bearing



Gear Data ($\alpha = 20^{\circ}$)		Mounting Holes		
Pitch diam	eter of gear (D_2)	22.000 in	Inner Ring Bolt Circle (L _i)	23.630 in
Diametral pitch (P _d)		4	Inner Ring Hole Count	18
Max Gear Tooth Load (F ₂)		6,400 lbs	Outer Ring Bolt Circle (L _o)	28.380 in
Number of Teeth (Z ₂)		88	Outer Ring Hole Count	12
Also Avail	able		Load Capacities	
14 SD Tooth Mating Pinion		SP1629-14	Moment Rating	50,150 ft-lbs
17 SD Tooth Mating Pinion		SP1629-17		
Interchan	ge			
Rotek	L6-25N9ZAvon	725 MB1Kaydon RK6-25N1Z		

866.294.5841 425.222.7535

sales@silverthin.com

8152 - 304th Ave. S.E. PO Box 5012 Preston, WA 98050-5012 USA

Copyright © 2024 All rights reserved by Silverthin