
# SILVERTHINSK6-29NZ

# Internal Gear Slewing Ring Bearing

#### **Overall Dimensions**

Outside diameter of outer ring (D <sub>o</sub> )	33.390 in
Internal diameter on outer ring (D <sub>i</sub> )	29.213 in
External diameter on outer ring (D <sub>r</sub> )	30.870 in
Inside diameter of inner ring (d <sub>i</sub> )	25.600 in
External diameter on inner ring (d <sub>o</sub> )	29.134 in
Approximate Weight	121.00 lbs



# Gear Data ( $\alpha = 20^{\circ}$ )

Pitch diameter of gear (D <sub>2</sub> )	26.000 in
Diametral pitch (P <sub>d</sub> )	4
Max Gear Tooth Load (F <sub>2</sub> )	6,300 lbs
Number of Teeth (Z <sub>2</sub> )	104

#### Also Available

14 SD Tooth Mating Pinion	SP1629-14
17 SD Tooth Mating Pinion	SP1629-17

## **Mounting Holes**

Inner Ring Bolt Circle (L <sub>i</sub> )	27.630 in
Inner Ring Hole Count	18
Outer Ring Bolt Circle (L <sub>o</sub> )	32.250 in
Outer Ring Hole Count	15

# **Load Capacities**

Moment Rating 53,100 ft-lbs

### Interchange

Rotek L6-29N9ZAvon 729 MB1Kaydon RK6-29N1Z

866.294.5841

425.222.7535

sales@silverthin.com

8152 - 304th Ave. S.E. PO Box 5012 Preston, WA 98050-5012 USA

Copyright © 2024 All rights reserved by Silverthin