
SILVERTHINSK6-33EZ

External Gear Slewing Ring Bearing

Overall Dimensions

Outside diameter of outer ring (D _o)	37.200 in
Internal diameter on outer ring (D _i)	33.150 in
Inside diameter of inner ring (d _i)	28.900 in
Internal diameter on inner ring (d _r)	31.420 in
External diameter on inner ring (d _o)	33.070 in
Approximate Weight	152.00 lbs



Gear Data ($\alpha = 20^{\circ}$)

Pitch diameter of gear (D ₂)	36.667 in
Diametral pitch (P _d)	3
Max Gear Tooth Load (F ₂)	7,580 lbs
Number of Teeth (Z ₂)	110

Also Available

14 SD Tooth Mating Pinion	SP3343-14
17 SD Tooth Mating Pinion	SP3343-17

Mounting Holes

Inner Ring Bolt Circle (L _i)	30.000 in
Inner Ring Hole Count	18
Outer Ring Bolt Circle (L _o)	35.000 in
Outer Ring Hole Count	18

Load Capacities

Moment Rating 57,400 ft-lbs

Interchange

Rotek L6-33E9ZAvon 733 MA1Kaydon RK6-33E1Z

866.294.5841

425.222.7535

sales@silverthin.com

8152 - 304th Ave. S.E. PO Box 5012 Preston, WA 98050-5012 USA

Copyright © 2024 All rights reserved by Silverthir