
## SILVERTHINSK6-43NZ

## **Overall Dimensions**

Outside diameter of outer ring ( $D_o$ )	47.170 in	
Internal diameter on outer ring (D <sub>i</sub> )	43.071 in	
External diameter on outer ring (D <sub>r</sub> )	44.650 in	
Inside diameter of inner ring (d <sub>i</sub> )	39.133 in	
External diameter on inner ring $(d_o)$	42.992 in	
Approximate Weight	188.00 lbs	

## Internal Gear Slewing Ring Bearing



Gear Data ( $\alpha = 20^{\circ}$ )		Mounting Holes	
Pitch diameter of gear ( $D_2$ )	39.667 in	Inner Ring Bolt Circle (L <sub>i</sub> )	41.500 in
Diametral pitch (P <sub>d</sub> )	3	Inner Ring Hole Count	24
Max Gear Tooth Load (F <sub>2</sub> )	8,340 lbs	Outer Ring Bolt Circle (L <sub>o</sub> )	46.000 in
Number of Teeth $(Z_2)$	119	Outer Ring Hole Count	18
Also Available		Load Capacities	
14 SD Tooth Mating Pinion	SP3343-14	Moment Rating	74,900 ft-lbs
17 SD Tooth Mating Pinion	SP3343-17		
Interchange			
Rotek L6-43N9ZAvo	n 742 MB1Kayde	on RK6-43N1Z	

866.294.5841 425.222.7535

35 sales@silverthin.com

8152 - 304th Ave. S.E. PO Box 5012 Preston, WA 98050-5012 USA

Copyright © 2024 All rights reserved by Silverthin