

SILVERTHIN SM08008ARO 80 mm Open Type A Thin Section Bearing

Specifications

Bore (B)	80.000 mm
Outside Diameter (D)	96.000 mm
Width	8mm
Land Diameter (L ₁)	85.900 mm
Land Diameter (L ₂)	90.100 mm
Land Diameter (L ₃)	92.200 mm
Approximate Weight	0.12 kg
Separator	Brass; one piece pocket separator
Precision Class	ABEC Class 1
Bearing Type	Angular Contact (Type A)
Seals, Shields	None (Open)
Unit System	Metric

Load Capacities


Static Radial Load	9,875 n
Dynamic Radial Load	4,605 n
Static Thrust Load	28,465 n
Dynamic Thrust Load	10,695 n

Interchange

Silverthin	SM08008ARO	Kaydon	K08008ARO	Kaydon	K08008ARO
------------	------------	--------	-----------	--------	-----------

Brass; one piece pocket separator

5/32" balls



1. Load capacities are not additive
2. The maximum shaft or housing fillet radius that the bearing corners will clear for this series is 0.8mm
3. Race Width Tolerance: +0.000 -0.127mm

Also Available

Open Radial Contact	SM08008CPO
Open 4-Point Contact	SM08008XPO
Open Duplexed (Back-to-Back)	SM08008BRO
Open Duplexed (Face-to-Face)	SM08008FRO