

# SILVERTHIN SM08008XPO 80 mm Open Type X Thin Section Bearing

## Specifications

Bore (B)	80.000 mm
Outside Diameter (D)	96.000 mm
Width	8mm
Land Diameter (L <sub>1</sub> )	85.900 mm
Land Diameter (L <sub>2</sub> )	90.100 mm
Approximate Weight	0.12 kg
Separator	Brass; snapover separator
Precision Class	ABEC Class 1
Bearing Type	4-Point Contact (Type X)
Seals, Shields	None (Open)
Unit System	Metric

## Load Capacities


Static Radial Load	8,430 n
Dynamic Radial Load	5,805 n
Static Thrust Load	21,040 n
Dynamic Thrust Load	8,720 n
Static Moment Load	370 N-m
Dynamic Moment Load	190 N-m

## Interchange

Silverthin	SM08008XPO	Kaydon	K08008XPO	Kaydon	K08008XPO
------------	------------	--------	-----------	--------	-----------

## Brass; snapover separator

5/32" balls



1. Load capacities are not additive
2. The maximum shaft or housing fillet radius that the bearing corners will clear for this series is 0.8mm
3. Race Width Tolerance: +0.000 -0.127mm

## Also Available

Open Angular Contact	SM08008ARO
Open Radial Contact	SM08008CPO
Open Duplexed (Back-to-Back)	SM08008BRO
Open Duplexed (Face-to-Face)	SM08008FRO