

# SILVERTHIN SM13008ARO 130 mm Open Type A Thin Section Bearing

## Specifications

Bore (B)	130.000 mm
Outside Diameter (D)	146.000 mm
Width	8mm
Land Diameter (L <sub>1</sub> )	135.900 mm
Land Diameter (L <sub>2</sub> )	140.100 mm
Land Diameter (L <sub>3</sub> )	142.200 mm
Approximate Weight	0.17 kg
Separator	Brass; one piece pocket separator
Precision Class	ABEC Class 1
Bearing Type	Angular Contact (Type A)
Seals, Shields	None (Open)
Unit System	Metric

## Load Capacities


Static Radial Load	15,655 n
Dynamic Radial Load	6,070 n
Static Thrust Load	45,190 n
Dynamic Thrust Load	14,525 n

## Interchange

Silverthin	SM13008ARO	Kaydon	K13008ARO	Kaydon	K13008ARO
------------	------------	--------	-----------	--------	-----------

## Brass; one piece pocket separator

5/32" balls



1. Load capacities are not additive
2. The maximum shaft or housing fillet radius that the bearing corners will clear for this series is 0.8mm
3. Race Width Tolerance: +0.000 -0.127mm

## Also Available

Open Radial Contact	SM13008CPO
Open 4-Point Contact	SM13008XPO
Open Duplexed (Back-to-Back)	SM13008BRO
Open Duplexed (Face-to-Face)	SM13008FRO