

# SILVERTHIN SM13013ARO

# 130 mm Open Type A Thin Section Bearing

## Specifications

Bore (B)	130.000 mm
Outside Diameter (D)	156.000 mm
Width	13mm
Land Diameter (L <sub>1</sub> )	139.700 mm
Land Diameter (L <sub>2</sub> )	146.300 mm
Land Diameter (L <sub>3</sub> )	149.600 mm
Approximate Weight	0.41 kg
Separator	Brass; one piece pocket separator
Precision Class	ABEC Class 1
Bearing Type	Angular Contact (Type A)
Seals, Shields	None (Open)
Unit System	Metric

## Load Capacities


Static Radial Load	24,710 n
Dynamic Radial Load	11,475 n
Static Thrust Load	71,300 n
Dynamic Thrust Load	26,955 n

## Interchange

Silverthin	SM13013ARO	Kaydon	K13013ARO	Kaydon	K13013ARO
------------	------------	--------	-----------	--------	-----------

## Brass; one piece pocket separator

1/4" balls



1. Load capacities are not additive
2. The maximum shaft or housing fillet radius that the bearing corners will clear for this series is 1.5mm
3. Race Width Tolerance: +0.000 -0.127mm

## Also Available

Open Radial Contact	SM13013CP0
Open 4-Point Contact	SM13013XP0
Open Duplexed (Back-to-Back)	SM13013BR0
Open Duplexed (Face-to-Face)	SM13013FR0