

SILVERTHIN SM14013ARO 140 mm Open Type A Thin Section Bearing

Specifications

Bore (B)	140.000 mm
Outside Diameter (D)	166.000 mm
Width	13mm
Land Diameter (L ₁)	149.700 mm
Land Diameter (L ₂)	156.300 mm
Land Diameter (L ₃)	159.500 mm
Approximate Weight	0.44 kg
Separator	Brass; one piece pocket separator
Precision Class	ABEC Class 1
Bearing Type	Angular Contact (Type A)
Seals, Shields	None (Open)
Unit System	Metric

Load Capacities


Static Radial Load	26,355 n
Dynamic Radial Load	11,920 n
Static Thrust Load	76,060 n
Dynamic Thrust Load	28,135 n

Interchange

Silverthin	SM14013ARO	Kaydon	K14013ARO	Kaydon	K14013ARO
------------	------------	--------	-----------	--------	-----------

Brass; one piece pocket separator

1/4" balls



1. Load capacities are not additive
2. The maximum shaft or housing fillet radius that the bearing corners will clear for this series is 1.5mm
3. Race Width Tolerance: +0.000 -0.127mm

Also Available

Open Radial Contact	SM14013CPO
Open 4-Point Contact	SM14013XP0
Open Duplexed (Back-to-Back)	SM14013BR0
Open Duplexed (Face-to-Face)	SM14013FR0