

SILVERTHIN SM20008XPO 200 mm Open Type X Thin Section Bearing

Specifications

Bore (B)	200.000 mm
Outside Diameter (D)	216.000 mm
Width	8mm
Land Diameter (L ₁)	205.900 mm
Land Diameter (L ₂)	210.100 mm
Approximate Weight	0.23 kg
Separator	Brass; snapover separator
Precision Class	ABEC Class 1
Bearing Type	4-Point Contact (Type X)
Seals, Shields	None (Open)
Unit System	Metric

Load Capacities


Static Radial Load	20,060 n
Dynamic Radial Load	9,720 n
Static Thrust Load	50,130 n
Dynamic Thrust Load	15,570 n
Static Moment Load	2,085 N-m
Dynamic Moment Load	760 N-m

Interchange

Silverthin	SM20008XPO	Kaydon	K20008XPO	Kaydon	K20008XPO
------------	------------	--------	-----------	--------	-----------

Brass; snapover separator

5/32" balls



1. Load capacities are not additive
2. The maximum shaft or housing fillet radius that the bearing corners will clear for this series is 0.8mm
3. Race Width Tolerance: +0.000 -0.127mm

Also Available

Open Angular Contact	SM20008ARO
Open Radial Contact	SM20008CPO
Open Duplexed (Back-to-Back)	SM20008BRO
Open Duplexed (Face-to-Face)	SM20008FRO