

SILVERTHIN SM25008XPO 250 mm Open Type X Thin Section Bearing

Specifications

Bore (B)	250.000 mm
Outside Diameter (D)	266.000 mm
Width	8mm
Land Diameter (L ₁)	255.900 mm
Land Diameter (L ₂)	260.100 mm
Approximate Weight	0.28 kg
Separator	Brass; snapover separator
Precision Class	ABEC Class 1
Bearing Type	4-Point Contact (Type X)
Seals, Shields	None (Open)
Unit System	Metric

Load Capacities


Static Radial Load	25,000 n
Dynamic Radial Load	11,120 n
Static Thrust Load	62,515 n
Dynamic Thrust Load	18,035 n
Static Moment Load	3,225 N-m
Dynamic Moment Load	1,075 N-m

Interchange

Silverthin **SM25008XPO** Kaydon **K25008XPO** Kaydon **K25008XPO**

Brass; snapover separator

5/32" balls



1. Load capacities are not additive
2. The maximum shaft or housing fillet radius that the bearing corners will clear for this series is 0.8mm
3. Race Width Tolerance: +0.000 -0.127mm

Also Available

Open Angular Contact	SM25008ARO
Open Radial Contact	SM25008CPO
Open Duplexed (Back-to-Back)	SM25008BRO
Open Duplexed (Face-to-Face)	SM25008FRO